



AQUATIC
TECHNOLOGIES

*The
Water
Treatment
Experts*

PRODUCT: DAM STOP LEAK® PROFESSIONAL

TARGET: LEAKING PONDS & DAMS



Easy application



Before using
Dam Stop Leak® Professional



After using
Dam Stop Leak® Professional

*Plug your leaking pond or dam quickly and easily
with **Dam Stop Leak® Professional**.*

WHY USE DAM STOP LEAK® PROFESSIONAL?

- ✓ Plugs leaks in clay and earth-based ponds or dams
- ✓ Contains NO Potassium
- ✓ Long-lasting - becomes a part of the dam wall
- ✓ Maintains better water quality
- ✓ Apply to full OR partially full water bodies
- ✓ Easy to apply

APPLICATION RATES

SIZE	COVERAGE
1kg	17m ²
5kg	83m ²
15kg	250m ²
18kg	300m ²

SAFE FOR



ALL SOIL TYPES

Works in clay, loam, sandy and rocky soils



FAST & SLOW LEAKS

Repairs fast leaks and slow seepage



WALLS & BASES

Works on both walls and bases



SAFE & LONG LASTING

Provides a safe, durable, flexible seal

HOW IT WORKS

Dam Stop Leak® Professional is made from 100% granulated polymers in different sizes, designed to help seal a range of dam leaks. When applied to the surface of the dam, the granules sink into the water and are naturally drawn towards cracks, gaps and seepage points. Larger granules help seal larger openings, while smaller granules work their way into fine cracks and slow-seeping leaks. The different polymer sizes allow for better coverage while using less product, helping to create a long-lasting seal that becomes part of the dam structure.



AQUATIC
TECHNOLOGIES

The Water Treatment Experts!

For more information visit
WWW.AQUATICTECHNOLOGIES.COM.AU



CLICK OR SCAN TO RE-ORDER

Use Dam Stop Leak® Professional in clay or natural based dams where water is present over the leak.

HOW DAM STOP LEAK® PROFESSIONAL WORKS



SUITABLE FOR



Dam Stop Leak® Professional

APPLICATION RATES

WHERE TO USE	APPLICATION RATE	HOW TO APPLY	HOW OFTEN TO APPLY
Dams, Lakes, and Ponds including Irrigation and Stock Watering Dams. Suitable for fast and slow leaks and all soil types.	60 grams of Dam Stop Leak® Professional per m² of water surface area.	Spread over the water's surface with an appropriate applicator or by hand. Use a targeted application if the location of the leak is known OR treat the entire water surface area.	Once, or as required.

FOR BEST RESULTS:

- ✓ Water should be present in the water body and above the area identified for treatment
- ✓ Apply when water temperature is above 5°C
- ✓ Apply when wind conditions are light
- ✓ Ensure area is free of excessive aquatic vegetation and algae

CLICK OR SCAN THE QR CODE BELOW TO WATCH OUR VIDEOS

OUR HOW-TO VIDEOS COVER:

1. What is Dam Stop Leak® Professional, What It Treats and Where You Can Use It
2. How Much to Use
3. How to Apply
4. What to Expect

HOW-TO VIDEOS



SAFETY DIRECTIONS

-  AVOID BREATHING DUST BY WEARING A MASK
-  WEAR PROTECTIVE GLOVES AND SAFETY GLASSES WHEN HANDLING
-  REFER TO THE SAFETY DATA SHEET FOR FURTHER INFORMATION



Head Office: 41 Yazaki Way, Carrum Downs, Vic. Australia 3201
www.AQUATICTECHNOLOGIES.com.au